H-462/2 DC current (neutral monostable)

HENGSTLER
K A C O





Inaktives Teil

HOZ-03462/24-001306-330/084.00 Artikel-Nr.: 462-1313

Generell

Sleeving:	Special feature:	Connections:
Open	forcibly guided contact set	Soldering pins
Contact set:	**Dimensions:**	**Weight:**
330	67,4x20,5x48,6 mm	115 g

Technical Data T_u = 20°C

Switching voltage,max	AC 230/240 V	DC 300 V
Switch. capacity,max 2.000/120 VA/W	Switching current,max 10 A	Constant current,max 10 A
Contact resistance<100mOhm		
Endurance,mech. >1x10 ^{7}	Endurance,electr.	1x10^{5} Switching cycle
Switching capacity	AC15 230/240 V, I_e	DC13 24 V, I_e
AgCdO-10 / 5 µm Au	4 A	2 A

Insulation	AC 120 V	AC 240 V	AC 230 V	AC 400 V	**Test voltage**
contact-contact	D-I	D-I	B-I	B-I	2.500V
contact set drive	D-I	D-I	B-I	B-I	2.500V

D-I = Reinforced (double) insulation B-I = Basic insulation

switch time energizing with 1,5*U

$t_{a-ö}$	t_{a-s}	$t_{r-ö}$	t_{r-s}
17 ms	23 ms	5 ms	7 ms

Shock resistance at16 ms 10 g Vibration resistance at10-55 Hz 10 g Ambient temperature -25...+80°C

Operating voltage

	coil I: R = 10000,0 Ohm				U_{nenn} +10/ -15%				
T_u/°C	U_1	U_2	U_3	$U_{rück}$	min	max			
20	86,0	199,7	205,4	14,7	107,6	181,6			V
20	86,0	199,7	205,4	14,7	107,6	181,6			V
20	86,0	199,7	205,4	14,7	107,6	181,6			V

All data do not represent any binding characteristics and may be subject to technical alterations.

Hengstler GmbH GB Bauelemente, Postfach 1249, D - 78 561 Wehingen, Tel: + 49 (7426) 68-0,Fax: + 49 (7426) 68-281