



HOZ-33462/14-001311-310/079.00 Article No.:462-1384

General

Enclosure: Open	Special feature: forcibly guided contact set	Connections: Soldering pins
Contact set (NO/NC/CO) 310	Dimensions: 57,8x20,5x48,6 mm	Weight: 90 g

Technical Data $T_u = 20^\circ\text{C}$

Switching voltage,max	AC 230/240 V	DC 300 V
Switch. capacity,max 2.000/120 VA/W	Switching current,max 10 A	Constant current,max 10 A
Contact resistance < 100 mOhm		
Endurance, mech. > 1x10 ⁷	Endurance, electr.	> 10 ⁵ Switching cycles
Switching capacity	AC15 230/240 V, I _e	DC13 24 V, I _e
AgCdO-10 / 0,2 μm Au	4 A	2 A

Insulation	AC 120 V	AC 240 V	AC 230 V	AC 400 V	Test voltage
contact-contact	D-I	D-I	B-I	B-I	2.500V
contact sets - drive	D-I	D-I	B-I	B-I	2.500V

D-I = Reinforced (double) insulation B-I = Basic insulation

Switch time energizing with 1,5*U_i

t _{a-nc}	t _{a-no}	t _{r-no}	t _{r-nc}
17 ms	23 ms	5 ms	7 ms
Shock resistance at 16 ms 10 g	Vibration resistance at 10-55 Hz 10 g	Ambient temperature -25...+80°C	

Operating voltage

T _u /°C	coil I: R = 2700,0 Ohm				U _{nenn} +10/ -15%			
	U ₁	U ₂	U ₃	U _{rück}	min	max		
20	61,9	156,6	155,8	7,4	63,0	142,4		V
-5	55,8	171,1	140,6	6,7	56,8	155,6		V
20	61,9	156,6	155,8	7,4	63,0	142,4		V

Quoted data does not represent any binding characteristics and may be subject to technical alterations.

Hengstler GmbH GB Bauelemente, Postfach 1249, D - 78 561 Wehingen, Tel: + 49 (7426) 68-0, Fax: + 49 (7426) 68-281