



HOZ-03462/24-001306-420/086.00 Article No.: 462 086 00

General

Enclosure: Special Open	feature: forcibly guided contact set	Connections: Soldering pins
Contact set (NO/NC/CO) 420	Dimensions: 67,4x20,5x48,6 mm	Weight: 115 g

Technical Data $T_u = 20^\circ\text{C}$

Switching voltage,max	AC 230/240 V	DC 300 V
Switch. capacity,max 2.000/120 VA/W	Switching current,max 10 A	Constant current,max 10 A
Contact resistance < 100 mOhm		
Endurance,mech. > 1x10 ⁷	Endurance,electr. > 10	⁵ Switching cycles
Switching capacity	AC15 230/240 V, I _e	DC13 24 V, I _e
AgSnO ₂ -12p / 0,2 µm Au	4 A	2 A

Insulation	AC 120 V	AC 240 V	AC 230 V	AC 400 V	Test voltage
contact-contact	D-I	D-I	B-I	B-I	2.500V
contact sets - drive	D-I	D-I	B-I	B-I	2.500V

D-I = Reinforced (double) insulation B-I = Basic insulation

Switch time energizing with 1,5*U_i

t _{a-nc} 17 ms	t _{a-no} 23 ms	t _{r-no} 5 ms	t _{r-nc} 7 ms	Ambient temperature -25...+80°C
Shock resistance at 16 ms 10 g		Vibration resistance at 10-55 Hz 10 g		

Operating voltage

T _u /°C	coil I: R = 10000,0 Ohm				U _{nenn} +10/ -15%		
	U ₁	U ₂	U ₃	U _{rück}	min	max	
20	77,8	199,7	205,4	14,7	96,3	181,6	V
-5	70,2	218,3	185,3	13,2	86,8	198,4	V
20	77,8	199,7	205,4	14,7	96,3	181,6	V

Quoted data does not represent any binding characteristics and may be subject to technical alterations.

Hengstler GmbH GB Bauelemente, Postfach 1249, D - 78 561 Wehingen, Tel: + 49 (7426) 68-0, Fax: + 49 (7426) 68-281