



HOZ-03464/34-001208-530/034.00 Artikel-Nr.: 464-1488

Generell

Sleeving: Open	Special feature: forcibly guided contact set	Connections: Soldering pins
Contact set: 530	Dimensions: 77,4x20,5x48,6 mm	Weight: 120 g

Technical Data $T_u = 20^\circ\text{C}$

Switching voltage,max	AC 230/240 V	DC 300 V
Switch. capacity,max 2.000/120 VA/W	Switching current,max 10 A	Constant current,max 10 A
Contact resistance<100mOhm		
Endurance,mech. >1x10 ⁷	Endurance,electr. AC15 230/240 V, I _e	1x10 ⁵ Switching cycle
Switching capacity	4 A	DC13 24 V, I _e
AgSnO ₂ -12p / 0,2 µm Au		2 A

Insulation	AC 120 V	AC 240 V	AC 230 V	AC 400 V	Test voltage
contact-contact	D-I	D-I	B-I	B-I	2.500V
contact set drive	D-I	D-I	B-I	B-I	2.500V

D-I = Reinforced (double) insulation B-I = Basic insulation

switch time energizing with 1,5*U

t _{a-o}	t _{a-s}	t _{r-o}	t _{r-s}
22 ms	29 ms	5 ms	7 ms
Shock resistance at 16 ms 10 g	Vibration resistance at 10-55 Hz 10 g	Ambient temperature -25...+80°C	

Operating voltage

T _u /°C	coil I: R = 5750,0 Ohm				U _{nenn} +10/ -15%			
	U ₁	U ₂	U ₃	U _{rück}	min	max		
20	60,6	152,1	148,5	10,6	75,2	138,3		V
20	60,6	152,1	148,5	10,6	75,2	138,3		V
20	60,6	152,1	148,5	10,6	75,2	138,3		V

All data do not represent any binding characteristics and may be subject to technical alterations.

Hengstler GmbH GB Bauelemente, Postfach 1249, D - 78 561 Wehingen, Tel: + 49 (7426) 68-0, Fax: + 49 (7426) 68-281