



HOZ-03466/44-001223-550/080.00 Artikel-Nr.: 466-1399

Generell

| | | |
|---------------------|---|--------------------------------|
| Sleeving: Open | Special feature: forcibly guided contact set | Connections: Soldering pins |
| Contact set: 550 | Dimensions: 87,4x66,5x20,5 mm | Weight: 135 g |

Technical Data $T_u = 20^\circ\text{C}$

| | | |
|-------------------------------------|--|-----------------------------------|
| Switching voltage,max | AC 230/240 V | DC 300 V |
| Switch. capacity,max 2.000/120 VA/W | Switching current,max 10 A | Constant current,max 10 A |
| Contact resistance < 100 mOhm | | |
| Endurance,mech. > 1x10 ⁷ | Endurance,electr. AC15 230/240 V, I _e | 1x10 ⁵ Switching cycle |
| Switching capacity | 4 A | DC13 24 V, I _e |
| AgSnO ₂ -12p / 5 μm Au | | 2 A |

| Insulation | AC 120 V | AC 240 V | AC 230 V | AC 400 V | Test voltage |
|-------------------|----------|----------|----------|----------|--------------|
| contact-contact | D-I | D-I | B-I | B-I | 2.500V |
| contact set drive | D-I | D-I | B-I | B-I | 2.500V |

D-I = Reinforced (double) insulation B-I = Basic insulation

switch time energizing with 1,5*U

| | | | |
|--------------------------------|---------------------------------------|---------------------------------|------------------|
| t _{a-o} | t _{a-s} | t _{r-o} | t _{r-s} |
| 23 ms | 29 ms | 5 ms | 7 ms |
| Shock resistance at 16 ms 10 g | Vibration resistance at 10-55 Hz 10 g | Ambient temperature -25...+80°C | |

Operating voltage

| T _u /°C | coil I: R = 96,0 Ohm | | | | U _{nenn} +10/ -15% | | | |
|--------------------|----------------------|----------------|----------------|-------------------|-----------------------------|------|--|---|
| | U ₁ | U ₂ | U ₃ | U _{rück} | min | max | | |
| 20 | 8,8 | 19,8 | 18,6 | 1,3 | 11,1 | 18,0 | | V |
| 20 | 8,8 | 19,8 | 18,6 | 1,3 | 11,1 | 18,0 | | V |
| 20 | 8,8 | 19,8 | 18,6 | 1,3 | 11,1 | 18,0 | | V |

All data do not represent any binding characteristics and may be subject to technical alterations.

Hengstler GmbH GB Bauelemente, Postfach 1249, D - 78 561 Wehingen, Tel: + 49 (7426) 68-0, Fax: + 49 (7426) 68-281